

Inhaltsverzeichnis

Produkt	Artikelnummer	EAN
Pro Venturix S90 Nahtbrenner Set - DIN	348290	7314523482902

Medien

Product Image



MamfileID: 363642

348290_Pro Ventuix HoseReg S90 Burner Kit DIN Kombi_product image_2.tif

FileType: tif

Beschreibung:

MamfileID: 363640

348290_Pro Ventuix HoseReg S90 Burner Kit DIN Kombi_product image_3.tif

FileType: tif

Beschreibung:

Hauptbild



MamfileID: 363641

348290_Pro Ventuix HoseReg S90 Burner Kit DIN Kombi_product image.tif

FileType: tif

Beschreibung:

Allgemein

Label	Pro Venturix S90 Nahtbrenner Set - DIN
Article Number	348290
EAN	7314523482902
Tariff Code	84.681.000
Country of Origin	Estonia
Applications	Dachabdichtung

Marketing

Product Description

Das Sievert Pro Venturix-System ist die nächste Generation der Dachbrenner. Es steht für maximale Sicherheit, Effizienz und benutzerfreundlicher Anwendung in einem Paket. Diese neu patentierte, PRO Venturix genannte, Brennertechnologie sorgt für eine vollständige, sichere und effiziente Gasverbrennung und senkt den Gasverbrauch auf ein Minimum. Konzipiert für effizientes Überlapp Verschweißen mit einer Schweißbreite von 90mm. Das spezielle Design garantiert minimale Reibung in der Schweißbahn und sorgt einfache Bedienung. Das Schlauchset hat eine Länge von 10m und kann dank POL Anschluss an alle Gasflaschen, die über diesen Anschluss verfügen, angeschlossen werden.

Stammdaten

Net weight	3.860 g
SKU weight	4.570 g
Packaging weight	710 g
Transport box net weight	500 g
Transport box total weight	5070 g

Stammdaten

(Net) Length x Width x Height	1.190 X 90 X 95 mm
(SKU) Length x Width x Height	900 X 140 X 140 mm
(Packaging) Length x Width x Height	900 X 140 X 140 mm
(Transport box) Length x Width x Height	1.140 X 250 X 210 mm
Volume	59.850.000 mm ³
SKU packaging quantity	1
Transport box packaging quantity	1

Technische Daten

Handle Working Pressure	1,5 - 4 bar
Precise Flame Adjustment	Ja
Neck Tube Length	750 mm
Burner Working Pressure	3,7 bar
Burner Dimension Flat	90 mm x 22 mm
Burner Gas Consumption	650 g/h
Burner Noise Level	78 dB
Propane Hose Length	10 m
Propane Hose Inner Diameter	6,3 mm
Propane Hose Outer Diameter	11,3 mm
Propane Hose Nipple Diameter	4,6 mm
Pressure Regulation Device Working Pressure	1 - 4 bar
Pressure Regulation Device Max Capacity	5 - 12 kg/h
Burner Effect	8,3 kW
Burner Diameter	
Material	Messing Plastik / Gummi Titanium
System Code	R
Handle Included	Ja
Handle Connection	BSP 3/8" LH
Burner Connection	Gewindeanschluss M20x1
Interchangeable Burners	Ja
Ignition Type	Bedienungsanleitung
Soft Grip	Ja
Pilot Flame	Ja
Preset Pilot Flame	Ja
Propane Hose Type	fest
Handle Hook Type	Integriert
Neck Tube Included	Ja

Technische Daten

Neck Tube Handle Thread Connection	G 3/8"-19
Neck Tube Burner Thread Connection	M20x1
Neck Tubes Accessories (Hook, Stand)	Standfuss
Burners Included	Ja
Burner Flame Type	Starkbrenner Flamme
Propane Hose Included	Ja
Propane Hose Connection	BSP 3/8" LH / BSP 3/8" LH
Pressure Regulation Device Included	Ja
Type Of Pressure Regulation Device Included	Druckregler, einstellbar mit Schlauchbruchsicherung (SBS)
Pressure Regulation Device Hose Connection	BSP 3/8" LH
Pressure Regulation Device Cylinder Connection	DIN Kombi
Burners Art No	696090
Handle Art No	348876
Neck Tube Art No	355669
Propane Hose Art No	770038
Pressure Regulation Device Art No	306315
Transport Packaging Type	Kartonverpackung
Packaging Type	Leinentasche

Crossselling